



GrüloKan 250 Inliner

With polyamide inliner

GrüloKan 250 Inliner offers you - besides all the advantages of a common rubber sewer cleaning hose - an extremely smooth polyamide inliner, which guarantees an obviously lower pressure drop. This minimisation of the pressure drop leads to a reduction of the engine speed which means considerable savings in fuel costs. This offers an efficiency benefit you should not miss! **GrüloKan 250 Inliner** is recommended especially for water conditioning and water recycling vehicles.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Temperature range: -40 °C to +70 °C

Standard Length: 60 m, 80 m, 120 m, 160 m, 180 m, 200 m, 220 m, 240 m
further lengths on request

Availability: 10 m up to 240 m

Colour: Black

Construction

Cover: NR/SBR, highly abrasion resistant, smooth

Reinforcement: Twofold braided synthetic fibres

Inliner: Polyamide, white

Lining: NR/SBR, black, smooth

Marking: Transfer tape G+L Ellipse GrüloKan Inliner 250 bar DN [..]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	7,00	250	625	100	0,830	10666-025

Reliable, for sure!