

# Perforated Metal Plank Type BP

Perforated metal planks, type BP "parallel", are characterised by their smooth line profiling and high loading capacity. For this reason this type is frequently used when large areas have to be covered in industrial areas and where stringent demands are made on load bearing capacity. This type can also be supplied without holes and is therefore ideal for use in the shelving construction sector.

## Technical Details

Material	Steel S235JR:	1,5 mm, 2,0 mm, 2,5 mm, 3,0 mm
	Stainless Steel:	1,5 mm, 2,0 mm,
	Aluminium:	2,0 mm, 2,5 mm
Surface treatment	Steel:	untreated, hot-dip galvanized, pre-galvanized
	Stainless Steel:	untreated, pickled
	Aluminium:	untreated, pickled, anodized
Free cross section	Max. ~ 27,2 %	
Width	150 mm, 200 mm, 250 mm, 300 mm (other widths possible in demand)	
Height	30 mm, 50 mm, 75 mm, 100mm, 150 mm (Corresponding to width and statical specification)	
Ball proof	Ø 20 mm – ball with Ø 20 mm can't fall through	
Slip resistance	R11 / V10 (Steel hot-dip galvanized)	
Longitudinal grid	125 mm (62,5 mm)	
Production length	max. 10 m, depending transport limited	

