

Filter regulator »FUTURA«, PC, Size 4, G 1, 0.5-8 bar, Fully a.

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 4, G 1, Control range 0.5-8 bar, Fully. Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

4047322245494

Article number	**100129**
Type number	**FU 6121**
Your price:	**268,09 € / Stk**

Scale of prices:

amount	Price	Unit
1	268,09 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	85
B [mm]	343
Bowl	Polycarbonate container with protective cage
C [mm]	137
Condensate drain	Fully-automatic
Connecting thread	Material: Die-cast zinc
Diaphragms	NBR
Filter element	Cellpor (PE)
Filter rating [µm]	5
Flow rate [l/min]	13000
Flow rate measurement	At P₁ = 10 bar, P₂= 6.3 bar and pressure drop Δ_p= 1 bar
Housing	PA66 GF60

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Max. control range [bar]	8
Max. input pressure [bar]	16
Max. internal air consumption	1.5 l/min (depending on secondary pressure)
Max. temperature range [°C]	50
Medium	Compressed air, neutral gases
Min. control range [bar]	0.5
Min. input pressure [bar]	1.5
Min. temperature range [°C]	-10
Page No.	HK033
Pressure gauge display max. [bar]	10
Pressure gauge display min. [bar]	0
Sealant	NBR
Series	FUTURA
Size	4
Thread	G 1