




Glycerine pressure gauge, CrNi steel, G 1/2, 0 - 2.5 bar, Ø 100

Glycerine pressure gauge CrNi steel design, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measure. range 0 - 2.5 bar, Ø 100. Glycerine-filled bourdon-tube pressure gauge, CrNi steel type. For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measurements in areas with high, dynamic pressure loads and vibration levels. Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.



4047322484039

Article number	134032
Type number	4191/1
Your price:	230,59 € / Stk

Scale of prices:

amount	Price	Unit
1	230,59 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Accuracy class	1
Connection	G 1/2
Connection position	rear, excentrical
Diameter [mm]	100
Front glass	Laminated safety glass
Lower / Upper range limit	Positive pressure
Material	CrNi steel
Max. ambient temperature [°C]	60
Max. medium temperature [°C]	100
Measuring range max. bar	2.5

Measuring range min. bar	0
Min. ambient temperature [°C]	-20
Page No.	HK214
Scale graduation in the bar area [bar]	0.05
Type	233.50