

Start up valve »multifix-mini«, Size 0, G 1/4

Start up valve »multifix-mini«, Size 0, G 1/4, Input pressure min. 2.5 bar, max. 16 bar, Medium / ambient temperature max. 60 °C. Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. With adjustable restrictor!

4047322123785

Article number	**100414**
Type number	**A 06**
Your price:	**48,17 € / Stk**

Scale of prices:

amount	Price	Unit
1	48,17 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	45
B [mm]	77.5
C [mm]	48.5
D [mm]	29
Flow rate [l/min]	2250
Flow rate measurement	At P₁= 6 bar and pressure drop Δ_p = 1 bar
Housing	Die-cast zinc
Max. ambient temperature [°C]	60
Max. input pressure [bar]	16
Max. medium temperature [°C]	60
Min. input pressure [bar]	2.5
Page No.	HK076

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Sealant	NBR
Series	multifix-mini
Size	0
Thread	G 1/4